



REVISED JUNE 2006

APEX ENGINEERING PRODUCTS CORPORATION

1241 Shoreline Drive

Aurora, Illinois 60504

Phone: 800-451-6291 FAX: 630-820-8886

Emergency Telephone Number: 630-820-8888

MATERIAL SAFETY DATA SHEET

PRODUCT INFORMATION

TRADE NAMES OR SYNONYMS: RYDLYME, RID-LIME
FORMULA: PROPRIETARY, CONFIDENTIALITY REQUIRED
CHEMICAL FAMILY: WATER SCALE CLEANER

HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENT	TLV (p.p.m.)	PEL (p.p.m.)	APPROXIMATE %
HYDROGEN CHLORIDE, AQUEOUS	5	5	LESS THAN 10

NOTE: Laboratory tests indicate material to be BIODEGRADABLE. NSF approved for use in beverage, pharmaceutical, bottling, poultry, and other food processing plants. USFDA has no jurisdiction over the product, since it does not come in direct contact with food. Non-reportable under Sara Title 3: Section 311/312/313 Categorization. Not reportable under CERCLA.

PHYSICAL DATA

BOILING POINT:	101° C.
SOLUBILITY IN WATER:	MISCIBLE
SPECIFIC GRAVITY, (WATER=1):	1.045
VAPOR PRESSURE:	30 TORR.
VAPOR DENSITY, (AIR=1):	GREATER THAN 1
PERCENT VOLATILE BY VOLUME:	99.6
APPEARANCE:	DARK LIQUID
ODOR:	ROASTED ALMONDS
pH:	UNREADABLE, GENERALLY <3
EVAPORATION RATE, (WATER=1):	SLOW
PHYSICAL STATE:	LIQUID

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	NO FLASH POINT, EXTINGUISHES FLAME
EXTINGUISHING MEDIA:	DOES NOT SUPPORT COMBUSTION
SPECIAL FIRE FIGHTING PROCEDURES:	NONE-WATER WILL CONTROL, OR CO2/DRY CHEMICALS
UNUSUAL FIRE & EXPLSION HAZARDS:	NON-COMBUSTIBLE OR EXPLOSIVE. BREATHING APPARAUS RECOMMENDED



(continued)

HMIS

HEALTH:	0
FLAMMABILITY:	0
REACTIVITY:	0
PERSONAL PROTECTION:	B

HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:	SHOULD NOT BE CONSIDERED HAZARDOUS WHEN USED AS DIRECTED.
EMERGENCY & FIRST AID:	IF EYE/SKIN CONTACT, COPIOUS WATER RINSE. CONSULT PHYSICIAN. NOT TO BE TAKEN INTERNALLY. IF INGESTED-DO NOT INDUCE VOMITING-DRINK MILK, EGG WHITES, ETC. AS DIRECTED BY PHYSICIAN.

NOTE: ADVERSE EFFECTS ON HUMAN HEALTH ARE NOT EXPECTED FROM THE RYDLYME SOLUTION, BASED UPON 60+ YEARS OF USE WITHOUT REPORTED ADVERSE HEALTH INCIDENCE IN DIVERSE POPULATION GROUPS, INCLUDING EXTENSIVE USE IN THE U.S. ARMED FORCES.

REACTIVITY DATA

STABILITY:	STABLE
INCOMPATIBILITIES:	STRONG CAUSTICS
HAZARDOUS DECOMPOSITION PRODUCTS:	NONE
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR
CONDITIONS TO AVOID:	EXCESSIVE HEATING

SPILL AND DISPOSAL PROCEDURES

ACTION TO TAKE FOR SPILLS:	RINSE WITH COPIOUS AMOUNTS OF WATER TO DILUTE: SODIUM BICARBONATE MAY ALSO BE USED TO SOAK UP AND NEUTRALIZE LIQUID, IF NECESSARY.
DISPOSAL METHOD:	EXPENDED OR USED MATERIAL MAY BE DISPOSED OF DOWN SEWER WITH WATER FLUSH. MATERIAL IS BIODEGRADABLE-EVEN IN AS RECEIVED FORM.

SPECIAL HANDLING INFORMATION

VENTILATION:	1. LOCAL EXHAUST: NORMAL
	2. MECHANICAL: SUFFICIENT
	3. RESPIRATORY: NONE
PROTECTIVE GLOVES:	RECOMMENDED, SUCH AS NEOPRENE GLOVES.
EYE PROTECTION:	RECOMMENDED, SUCH AS CHEMICAL GOGGLES.
OTHER PROTECTIVE EQUIPMENT:	AS RECOMMENDED BY PLANT SAFETY DEPARTMENT. TO PREVENT STAINING OF CLOTHES, WEAR AN APRON.



(continued)

SPECIAL PRECAUTIONS

HANDLING AND STORING:

CAN MATERIAL BE STORED OUTSIDE?

IS MATERIAL FREEZABLE?

OTHER PRECAUTIONS:

PRESERVE INTEGRITY OF CONTAINER.

YES, MAINTAIN TEMPERATURE BETWEEN 10°-180° F.

YES.

Do not circulate material for more than a six hour period without consulting the

manufacturer. Most RYDLYME cleanings can be accomplished within an average of two-four hours. Please use material only as directed. Do not heat. Use RYDLYME at an ambient temperature. Vent circulating solution to atmosphere. Some adverse reactions may occur with some alloys of aluminum, magnesium, and/or zinc. Please consult the manufacturer.

FOR ADDITIONAL INFORMATION, PLEASE REVIEW THE RYDLYME SPECIFICATIONS OR CONTACT OUR MANUFACTURING FACILITY AT 800-451-6291.

This data is furnished independent of any sales of the product only for your investigation and independent verification. While information is believed to be correct, APEX ENGINEERING PRODUCTS CORPORATION shall in no event be responsible for any damage whatsoever, directly or indirectly, resulting from the publication or use of or reliance upon data contained herein. No warranty, either expressed or implied, of merchantability, of fitness, or of any nature with respect to the product, or to the data, is made herein. This MSDS has been reviewed by the U.S. Department of Labors' Chicago District Office.